

**Proven
Performance**

McCloskey
INTERNATIONAL
S190



S190 High Energy Screener

The highly advanced S190 is capable of screening a diverse range of material in the most difficult conditions. Designed to meet the demands of high throughput operations in quarrying, crusher circuits, sand & gravel, and coal screening.


"In a test run against two competitors, the McCloskey S190 met the demands we have in quality and production. We were able to go from 5mm to 4mm harpwire, and still have the same tonnage production for our concrete customers. That's why we now own four S190's."

Jan Sylvestersen
Production Manager, Jydsk Stenindustri, Denmark



Options


Roll in bogie system on track units.



Shredder.



Heavy duty single or double deck vibrating grid.



Feeder extension of 3ft (915mm), with capacity increased to 13.5yd³.



McCloskey
INTERNATIONAL

Features & benefits

Hydraulic screenbox linkage system -

Allows greater accessibility for screen change, and enables optimum screen coverage at varying screenbox angles.

Highly aggressive 20x5 (1600x1524mm) screenbox -

Provides the highest product capacity in its class.

Wedge system -




User friendly wedge system ensures faster screen change.


48" (1200mm) Feed conveyor -

For free flow of materials on the main conveyor. Optimised spreader plate ensures greater screen coverage, and wider chutes minimise potential spillage and blockages.

14ft (4267mm) Grid opening -

Allows the use of larger loading shovels.





S190 Dimensions and weight

| | |
|-------------------------------|-------------------------------------|
| Length - transport all models | 17.16m (56' - 4") |
| Width - transport all models | 2.90m (9' - 6") |
| Height - transport track | 3.40m (11' - 2") |
| Height - transport wheel | 3.68m (12' - 1") |
| Weight - track | 36,000 kgs (79,366 lbs) - estimated |
| Weight - wheel | 31,000 kgs (68,343 lbs) - estimated |

See it in action...
View working videos, customer testimonials and more at www.mccloskeyinternational.com



N.America & S.America
#1 McCloskey Road, RR#7
Peterborough, Ontario Canada,
K9J 6X8
1-877-Trommel
T (705) 295-4925
F (705) 295-4777
mccloskey@mccloskeyinternational.com

UK & International
47 Moor Road,
Coalisland,
Co Tyrone,
N.Ireland BT71 4QB
T +44 (0) 2887-740-926
F +44 (0) 2887-747-242
salesuk@mccloskeyinternational.com

McCloskey International reserves the right to make changes to the information and design of the machines on this brochure without reservation and notification to the users. McCloskey International assumes no liability resulting from errors or omissions in this document.



Standard Features



Durability

Branded components throughout- CAT Engine, David Brown Pumps, 2 Pack Paint system.

Heavy duty hardox steel.

Innovative design.

High efficiency diesel hydraulic system allows higher throughput and lower fuel consumption.



Maintenance/User friendly

Accessible engine bays.

Fixed galvanised walkways.


Universal user friendly controls throughout the McCloskey line.

10min setup time.

Highly maneuverable onsite.

Unique user friendly belt adjusters.

Universal dimensions allow meshes to be used throughout the McCloskey S Line.



Authorised dealer.